



Certified CE

Amplifier TSFA2-DGM-xx™



Scope of delivery (Options):

TSFA2-DGM-RB for one RetroBolt-ICA Sensor	Part# 303744
TSFA2-DGM-2RB for two RetroBolt-ICA Sensoren	Part# 303746
TSFA2-DGM-FS for one FS11CXK Sensor	Part# 303745
TSFA2-DGM-2FS for two FS11CXK Sensoren	Part# 303747
TSFA2-DGM-RBFS for one RetroBolt-ICA and one FS11CXK Sensor	Part# 303748

Dimensions (HxWxD in mm)	35 x 185 x 83
Housing	Aluminum
Weight	approx. 550 g
Protection class	IP66
Temperature range	Operation: 0 bis 60 °C Storage: -40 bis 90 °C
Relative humidity	0 to 95 % non-condensing
Mounting	two M4 screws
Gain	1, 2, 4, 8, 10, 20, 40, 80, 100, 200, 400, 800
Output signals	0 bis 10 V DC
Connections	PG9 and/or sensor-specific
Current consumption	175 mA bei +15 V DC, -19 mA bei -15 V DC
Sensor inputs	2
Sensor type	FS11 CXK-ICA or RetroBolt-ICA
Voltage supply	±15 V DC
Certification	CE, CSA, ETL

All warnings and other important, detailed information must be obtained from the operating manual. This document is not subject to an automatic revision service.