



VisionNG 10



Scope of delivery:

VisionNG 10

Part# 471001

VisionNG 10	
Dimensions (HxWxD in mm)	approx. 260 x 375 x 56
Housing	Chassis: Nickel Metal Front: Aluminum
Weight	approx. 2240 g
Protection class	IP65 from the front, with built-in seal IP 20 from the back
Temperature range	Operation: 0 to 50 °C Storage: -20 to 60 °C
Relative humidity	5 to 95 % non-condensing
Mounting	four mounting brackets or M3 screws
Operating system	Windows 10 IoT
Processor	Intel® Apollo Lake Series N4200
VGA	Intel HD Graphic Technology
Memory	4 GB DDR3L SO-DIMM 1866 MHz
Storage	mSATA 32 GB
Control panel	Integrated keyboard and mouse
Monitor	10,4" Touchscreen
Resolution	1024 x 768
Max. Colours	16.2 M
Angle of view	160 °
Luminance	400 cd / m2
Lighting	Back Light LED
Voltage supply	10 - 30 V DC 2 pole Connector
Power consumption	approx. 30 W 1.5 A (3 A at start)
USB	4 x USB 3.0 and 1 x USB 2.0 front connection
Ethernet	2 x Intel I210 Gigabit LAN
Monitor connection	HDMI
COM	RS-232 (9 pin D-SUB Male)

All warnings and other important, detailed information must be obtained from the operating manual. This document is not subject to an automatic revision service.