Vision LX7

Scope of delivery:
Vision LX7 complete Part# 480001

Required cables to connect to a
SPECTRA™ unit
Cat5 Ethernet Cable 5 m Part# 814012

Vision LX7	
Dimensions (HxWxD in mm)	130 x 200 x 45
Housing	Stainless steel
Weight	approx. 1100 g
Protection class	IP65 from the front, with built-in seal IP20 from the back
Temperature range	Operation: 0 to 45 °C Storage: -20 to 65 °C
Relative humidity	10 to 90 % non-condensing
Mounting	four M3 10 mm mounting bolts
Monitor size	7“ Touchscreen
Air Pressure	Max. 2000 m above MSL
Voltage supply	5 - 24 V DC, approx. 0,5 A
Chemical resistiveness	Ambient air must be free of high concentrations of acids, brine, salts, metallic vapors and other corrosive or electroconductive emissions.
Certification	CE

Interfaces	**Function**
2 x USB 2.0	Standard USB 2.0
Ethernet	Ethernet 10/100
Com	RS-232 (9 pin D-SUB)
3-pin receptacle	Voltage supply

All warnings and other important, detailed information must be obtained from the operating manual. This document is not subject to an automatic revision service.

Montronix GmbH
Benzstr. 7
D-71720 Oberstenfeld
Germany

Telephone: +49 7062 6793 00
Fax: +49 7062 6793 10
E-Mail: info@montronix.de
Internet: www.montronix.de