VisionNG 15

Scope of delivery:

VisionNG 15 Part# 4801001

VisionNG 15	
Dimensions (HxWxD in mm)	approx. 310 x 483 x 91
Housing	Chassis: Nickel Metal Front: Scratch-resistant gray paint on aluminum
Weight	approx. 5670 g
Protection class	IP65 from the front, with built-in seal IP 20 from the back
Temperature range	Operation: 0 to 50 °C Storage: -20 to 60 °C
Relative humidity	10 to 90 % non-condensing
Mounting	four mounting brackets or four screws
Operating system	Windows 10 IoT
Processor	Intel® Apollo Lake Series N4200
VGA	Intel HD Graphic Technology
Memory	4 GB DDR3L SO-DIMM 1866 MHz
Storage	mSATA 32 GB
Control panel	Integrated keyboard, touchpad and mouse
Audio	Realtek ALC262 HD
Monitor size	15“ Touchscreen
Resolution	1024 x 768
Max. Colours	16.2 M
Angle of view	160 °
Luminance	400 cd / m2
Lightning	Back Light LED
Voltage supply	10 - 30 V DC 3-pole Connector
Power consumption	approx. 30 W 1.5 A (3 A at start)
USB	4 x USB 3.0 and 2 x USB 2.0 front connection
Ethernet	2 x Intel I210 Gigabit LAN
Monitor connection	HDMI
COM	2 x RS-232 (9 pin D-SUB Male)

All warnings and other important, detailed information must be obtained from the operating manual. This document is not subject to an automatic revision service.

Montronix GmbH
Gottlieb-Daimler-Str. 53/1
D-71711 Murr
Germany

Telephone: +49 7144 15086 30
Fax: +49 7144 15086 31
E-Mail: info@montronix.de
Internet: www.montronix.com